


## Product: 733384021 (RSC 162/1 Ag)

|                                          |                                                                                                                                                    |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
|                                          |                                                                   |
|                                          | rolled engaging crimp contact (pin contact), B0 crimp                                                                                              |
| <b>Delivery informations</b>             |                                                                                                                                                    |
| Availability                             | available                                                                                                                                          |
| <b>Product description</b>               |                                                                                                                                                    |
| Description                              | rolled engaging crimp contact (pin contact), B0 crimp                                                                                              |
| Type                                     | RSC 162/1 Ag                                                                                                                                       |
| Order No.                                | 733 384-021                                                                                                                                        |
| Conductor size                           | 0.14 mm <sup>2</sup> to 0.5 mm <sup>2</sup>                                                                                                        |
| <b>Technical data</b>                    |                                                                                                                                                    |
| Type of termination                      | crimping                                                                                                                                           |
| Pin dimensions                           | 1.6 mm                                                                                                                                             |
| <b>Material</b>                          |                                                                                                                                                    |
| Contact material                         | Cu Zn                                                                                                                                              |
| Contact surface material                 | Ag                                                                                                                                                 |
| <b>Packing unit</b>                      |                                                                                                                                                    |
| Packaging unit                           | 100 pieces                                                                                                                                         |
| <b>Scope of delivery and accessories</b> |                                                                                                                                                    |
| Accessories to order separately          | suitable for NR-series and ST-series (5 pole) connectors<br>suitable crimping tool:<br>crimping pliers XZC 0701<br>suitable ejection tool: XWA 164 |
| <b>Picture</b>                           |                                                                                                                                                    |
| Drawing                                  |                                                                 |

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.